

DURATEQ® Docking Solutions

Durateq Docking Solutions are used in connection with Durateq ATV handheld media devices to create assistive technology solutions for public venues. The docking solutions enable a connection to an A/C power adapter for charging the battery and a USB cable connection for synchronization, programming, and file sharing with a PC. The docking solutions are available in two sizes: a single Charge/Sync Dock for charging a single unit, and a 5U Charge/Sync Dock which holds 5 units for simultaneous charging. The 5U dock offers the first dock for USB connection. Each dock features PO-GO Spring Pin contacts to the Durateq ATV units' waterproof connectors, non-slip rubber feet, and permanent mounting holes.

DURATEQ® Charge/Sync Dock

FOR INDOOR USE ONLY

Part # DD001A

Input: 100V-240V 50/60Hz 0.3A

Output: 5V 2A

Softeq Development Corp

www.softeq.com USA



DURATEQ® 5U Charge/Sync Dock

FOR INDOOR USE ONLY

Part # DD005A

Input: 100V-240V 50/60Hz 1.5A

Output: 5V 6A

Softeq Development Corp

www.softeq.com USA



Visit www.softeq.com/products.assistive.asp for more information or to request quote.

DURATEQ® Docking Solution Specifications

| | Single Charge/Sync Dock | 5U Charge/Sync Dock |
|--|--|--|
| Size: | 5-3/16" W x 2-3/16" D x 2-1/8" H | 19-15/16" W x 2-3/16" D x 2-1/8" H |
| USB Connector: | One Mini-USB B supporting USB 2.0 | One Mini-USB B supporting USB 2.0 (position one only) |
| Power Connector: | DC Power Jack, 2.5mm ID, 5.5mm OD | DC Power Jack, 2.5mm ID, 5.5mm OD |
| Input Power: | 5VDC 2.0A | 5VDC 6.0A |
| Recommended A/C Power Adapter: | Input: 100V-240V 50/60Hz 0.3A | Input: 100V-240V 50/60Hz 1.5A |
| | Output: 5V 2A | Output: 5V 6A |
| Cradle Connector: | PO-GO Spring Pin contacts for Durateq unit connector | PO-GO Spring Pin contacts for Durateq unit connector |
| Cradle Material: | Solid metal base | Solid metal base |
| | Heavy-Duty ABS plastic inserts with rubber guides | Heavy-Duty ABS plastic inserts with rubber guides |
| Mounting: | Non-Slip Rubber Feet and wall-mount holes in back of metal base | Non-Slip Rubber Feet and wall-mount holes in back of metal base |
| Recommended USB Cable: | USB A to Mini-USB B, Length 6 feet | USB A to Mini-USB B, Length 6 feet |
| Part Numbers: | DD001A (Blue) DD001K (Black) DD001Y (Yellow) DD001R (Red) | DD005A (Blue) DD005K (Black) DD005Y (Yellow) DD005R (Red) |
| Kit Price with cable and adapter: | \$99.00 | \$399.00 |

Visit www.softeq.com/products.assistive.asp for more information or to request quote.